Hose Camel Amflo Schrader Hose O.D. Clamp Camel Amflo NPT No No No Range Width No. No

6363

6362 6361

Solid Brass Male Hose Barb Fittings

Select fitting to match hose inside diameter. *All packages contain 10 fittings. Amflo part numbers with D suffix indicate display packs.

1/8"	1/8"		399
3/16"	1/8"		400
1/4"	1/8"	52-493	404
1/4"	1/4"		401
1/4"	1/4"	52-039	401D
5/16"	1/4"	52-038	405D
3/8"	1/4"	52-037	406
1/2"	1/4"	52-036	408
1/4"	3/8"		604
3/8"	3/8"	52-492	606
1/4"	3/8"-24		398
1/2"	3/8"		608
3/8"	1/2"		806
1/2"	1/2"	52-491	808
1/2"	3/4"		813
3/4"	3/4"		814
1"	3/4"		816
1"	1"		818

Hose Clamps

Gear type clamps permit quick hose repair

with simple tools. Stainless band, plated steel cerow 10 pack

strew. To path.		
1/4" to 5/8"	5/16"	580
3/8" to 7/8"	5/16"	581
1/2" to 1-1/4"	5/16"	582
3/4" to 1-3/4"	9/16"	583

	Camel	Amflo
Hose Size	No.	No.
Andrew Commission of the Commi		

Hose Splicer and Clamps Kits

Use to repair hose in-line repairs or install new hose end fittings.

1/4" Large Kit		410D
1/4" D-I-Y Kit	52-464	417D
3/8" Barb w/ clamp		411D
3/8" Hose Repair Kit		412D
oeste tid alexa otto parti. 2003.		

Male Ball Swivels

Fitting may swivel and rotate without kinking or twisting of hose.

1/4" 1/4" 4445 3/8" 1/4" 446S

Male Swivel Fittings

Permits rotation of fitting without kinking or twisting of hose.

1/4" 1/4" 401S 606S 3/8" 3/8" 2808 1/2" 1/2"

Hi-Volume Male Swivel Fittings 5/16 1/4" 4058


3/8" 1/4" 406S

Hose ID	NPT	Camel No.	Amflo No.	Hose ID	NPT	Camel No.	Amflo No.	Schrade No.
Solid E	Brass F	emale F	ittings "	One Pi	ece Fe	male Sw	vivel Fitt	ings

Permits rotation of fitting without kinking 52-042 441 1/4" 1/4" or twisting of hose. 5/16" 1/4" 451 3/8" 1/4" 461 1/4" 1/4" 443 3/8" 3/8" 661 3/8" 1/4" 463 1/2" 3/8" 681

Two	Piece Swivel	Female Fittings
1/4"	1/4"	442
5/16"	1/4"	452
3/8"	1/4"	462D
3/8"	3/8"	662L

Solid Brass Hose Splicers			
1/4"	52-046	402	7676
5/16"	52-045	502	
3/8"	52-044	602	7674
1/2"	52-047	802	

















CAUTION: Fittings must be secured to hose with either hose clamps or crimped-on ferrules with a hose crimper.

Hose barbs are intended for use on compressed air only with a maximum working pressure of 300 PSI.

Brass Hose Fittings

Lock-On Hose Barbs. Designed to use with Amflo's special lock-on hose. No ferrules or hose clamps are required. Not to be used with conventional hose. All lock-on packages contain 10 fittings unless otherwise marked.















Flow Passage	NPT	Amflo No.
Tank Safety Valve		

Safety valve is furnished with relief pressure preset. 1/4" NPT (125 PSI) 265-RET 1/4" 1/4" NPT (165 PSI) 267-RET

Hose ID	NP1 Thread	Amtlo No.
Lock-On Ho	se Barb Male	
1/4"	1/4"	401L
3/8"	1/4"	406L
3/8"	3/8"	606L
1/2"	1/2"	808L

Lock-On Hose Barb 2PC Female			
1/4"	1/4"	442L	
3/8"	3/8"	662L	

Lock-On Hos	e Barb Male Ball	Swivel
1/4"	1/4"	444SL
3/8"	1/4"	446SL

Lock-On Hose Barb Splicers	
1/4"	402L
3/8"	6021

Lock-On Hose Barb Kit. 35 piece kit. Assortment. 1/4" & 3/8"

Female Crosses

Excellent for running several air lines from a common supply hose. Solid brass.

1/4" NPT	344X
3/8" NPT	366X

Female Tees

Run two lines from a common feed. Solid brass.

toni tre	0 111100	III UIII U	COMMITTOR	loou.	Oona	DIG
1/4"	NPT				344	T
3/8"	MPT				366	Т

Three-Way Manifold

Strong machined aluminum construction. Each manifold accepts three outlet hoses or couplers. * 3404 and 3406 available in display packs.

1/4" NPTF	1/4" NPTF	3404*
3/8" NPTF	1/4" NPTF	3406*
1/2" NPTF	1/4" NPTF	3408
Flat Brass Contru	ction.	

3/8" NPTF 1/4" NPTF 3403RET **Angle Swivels**

Stop hoses from kinking or for use in pneumatic equipment applications. Brass.

1/4" male / female swivels	344R90
Brass In-Line Swivels	100

1/4" male / female NPT	344R
3/8" male / female NPT	366R

Uniswivel

Flow Passage

360° swivel action. 300 PSI.

1/4" NPTF x 1/4" NPTM 344U 344U-1 NPT

Amflo No.

Brass Drain Co	cks	1 6 1 1 1	
1/4"	1/4"	930	
1/16"	1/8"	931	



