



MARINE / INDUSTRIAL

Product	Page	Size	W.P.	Tube	Cover	Description
SS269	39	1" - 12½"	100 - 200	Nitrile	Nitrile	Softwall marine exhaust hose designed for transferring wet exhaust on marine engines.
SW369	40	1¼" - 6½"	100 - 200	Nitrile	Nitrile	High temperature hardwall marine exhaust hose and fuel fill connection.
SW469	40	½" - 3"	35 - 50	Nitrile	Nitrile	Hardwall marine fuel fill and vent hose.

SS269 SOFTWALL MARINE EXHAUST HOSE

- Heavy duty softwall marine exhaust hose for use as a flexible connection to transfer wet exhaust on marine engines.
- Heat resistant tube handles high temperatures found in marine engine compartments.
- Durable heat, ozone, and abrasion resistant cover.

Tube: Extruded specially compounded Nitrile.

Reinforcement: Textile.

Cover: Specially compounded Nitrile.

Temperature: -40° to +200°F.

Meets U.S.C.G TYPE Standards for specification SAE J2006 R1.



I.D.	O.D.	REINFORCEMENT	WORKING PRESSURE PSI	WEIGHT LB/FT
1"	1 ⁷ / ₁₆ "	2 plies	200	.46
1 ¹ / ₈ "	1 ⁹ / ₁₆ "	2 plies	200	.49
1 ¹ / ₄ "	1 ¹³ / ₁₆ "	2 plies	200	.69
1 ⁵ / ₁₆ "	1 ⁷ / ₈ "	2 plies	200	.71
1 ³ / ₈ "	1 ¹⁵ / ₁₆ "	2 plies	200	.75
1 ¹ / ₂ "	2 ¹ / ₁₆ "	2 plies	200	.82
1 ⁵ / ₈ "	2 ³ / ₁₆ "	2 plies	200	.87
1 ³ / ₄ "	2 ⁵ / ₁₆ "	2 plies	200	.92
1 ⁷ / ₈ "	2 ⁷ / ₁₆ "	2 plies	200	.97
2"	2 ⁹ / ₁₆ "	2 plies	200	1.07
2 ¹ / ₈ "	2 ¹¹ / ₁₆ "	2 plies	200	1.12
2 ¹ / ₄ "	2 ¹³ / ₁₆ "	2 plies	200	1.17
2 ³ / ₈ "	2 ¹⁵ / ₁₆ "	2 plies	200	1.25
2 ¹ / ₂ "	3 ¹ / ₁₆ "	2 plies	200	1.32
2 ⁵ / ₈ "	3 ³ / ₁₆ "	2 plies	200	1.37
2 ³ / ₄ "	3 ⁵ / ₁₆ "	2 plies	200	1.42
2 ⁷ / ₈ "	3 ⁷ / ₁₆ "	2 plies	200	1.52
3"	3 ⁹ / ₁₆ "	4 plies	200	1.46
3 ¹ / ₂ "	4 ¹ / ₁₆ "	4 plies	200	1.70
4"	4 ³ / ₁₆ "	4 plies	200	1.93
4 ¹ / ₂ "	5 ¹ / ₁₆ "	4 plies	200	2.21
5"	5 ¹⁵ / ₁₆ "	6 plies	200	3.80
5 ⁹ / ₁₆ "	6 ¹ / ₂ "	6 plies	200	4.14
6"	6 ¹⁵ / ₁₆ "	6 plies	200	4.51
6 ⁵ / ₈ "	7 ⁹ / ₁₆ "	6 plies	200	5.01
7"	7 ¹⁵ / ₁₆ "	6 plies	200	5.24
8"	8 ¹⁵ / ₁₆ "	6 plies	150	5.83
8 ⁵ / ₈ "	9 ¹ / ₂ "	6 plies	150	5.95
10"	10 ³ / ₄ "	6 plies	150	6.77
10 ³ / ₄ "	11 ⁵ / ₈ "	6 plies	100	7.55
12"	12 ⁷ / ₈ "	6 plies	100	8.38
12 ³ / ₄ "	13 ⁵ / ₈ "	6 plies	100	8.88

SW369 HARDWALL MARINE EXHAUST HOSE

U.S.C.G. Type Marine hose.



- Ultra-flexible, lightweight hardwall marine exhaust hose specifically designed to be a high temperature, wet exhaust and fuel fill flexible connection.
- Dual helix wire allows for tight bends without kinking.
- Specially formulated cover is heat and ozone resistant.

Tube: Extruded Nitrile.
Reinforcement: Textile with dual wire helix.
Cover: Specially compounded Nitrile.
Temperature: -40° to +200°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1 1/4"	1 11/16"	4"	200	.56	Full
1 3/8"	1 13/16"	4"	200	.59	Full
1 1/2"	2"	5"	200	.69	Full
1 5/8"	2 1/8"	5"	200	.75	Full
1 7/8"	2 3/8"	6"	200	.84	Full
2"	2 1/2"	6"	200	.88	Full
2 3/8"	2 7/8"	6"	150	1.26	Full
2 1/2"	3"	10"	150	1.33	Full
2 7/8"	3 1/8"	11"	125	1.62	Full
3"	3 3/8"	12"	125	1.68	Full
3 1/2"	4 1/8"	15"	125	1.94	Full
4"	4 3/8"	18"	125	2.51	Full
4 1/2"	5 1/8"	24"	100	2.78	Full
5"	5 3/8"	30"	100	3.04	Full
5 3/8"	6 3/16"	34"	100	3.38	Full
6"	6 3/8"	36"	100	3.79	Full
6 3/8"	7 1/4"	40"	100	4.25	Full

SW469 HARDWALL MARINE FUEL FILL HOSE

Meets U.S.C.G. Standards for specification SAE J1527 TYPE B2.



- Flexible, hardwall marine hose for use in fuel fill and vent applications on marine fuel systems.
- Specifically designed to handle high temperatures.

Tube: Extruded Nitrile.
Reinforcement: Textile with dual wire helix.
Cover: Specially compounded Nitrile.
Temperature: -40° to +200°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1/2"	7/8"	4"	50	.24	Full
5/8"	1"	4"	50	.28	Full
3/4"	1 1/8"	4"	50	.32	Full
7/8"	1 1/4"	4"	50	.36	Full
1"	1 3/8"	4"	50	.39	Full
1 1/8"	1 1/2"	4"	50	.44	Full
1 1/4"	1 5/8"	4"	50	.47	Full
1 3/8"	1 11/16"	4"	50	.49	Full
1 7/8"	1 3/4"	4"	50	.52	Full
1 1/2"	1 7/8"	4"	50	.56	Full
1 5/8"	2"	6"	50	.59	Full
1 3/4"	2 1/8"	6"	50	.63	Full
1 7/8"	2 1/4"	6"	50	.71	Full
2"	2 3/8"	6"	50	.78	Full
2 1/8"	2 1/2"	6"	50	.84	Full
2 1/4"	2 5/8"	6"	50	.91	Full
2 3/8"	2 3/4"	6"	50	.95	Full
2 1/2"	2 7/8"	10"	50	1.00	Full
2 5/8"	3"	10"	40	1.08	Full
2 3/4"	3 1/8"	10"	40	1.15	Full
2 7/8"	3 1/4"	10"	35	1.25	Full
3"	3 3/8"	12"	35	1.30	Full