


# JIC 37° Flare-Twin®

Female 37° JIC  
Swivel to Male  
Pipe Adapter



TUBE O.D.	MALE PIPE THREAD	CATALOG NUMBER
1/4	1/4	9100x4x4
5/16	1/4	9100x5x4
3/8	1/4	9100x6x4
3/8	3/8	9100x6x6
1/2	3/8	9100x8x6
1/2	1/2	9100x8x8
5/8	3/8	9100x10x6
5/8	1/2	9100x10x8
3/4	1/2	9100x12x8
3/4	3/4	9100x12x12
1	3/4	9100x16x12
1	1	9100x16x16
1-1/4	1-1/4	9100x20x20

90° Union Elbow  
(Ref. SAE No. 070201)  
Assembly Number  
C35505x4, etc.





TUBE O.D.	CATALOG NUMBER
1/4	C5505x4 <sup>1</sup>
5/16	C5505x5 <sup>1</sup>
3/8	C5505x6 <sup>1</sup>
1/2	C5505x8 <sup>1</sup>
5/8	C5505x10 <sup>1</sup>
3/4	C5505x12 <sup>1</sup>
1	C5505x16 <sup>1</sup>
1-1/4	C5505x20 <sup>1</sup>
1-1/2	C5505x24 <sup>1</sup>
1/4	TF5505x4
5/16	TF5505x5
3/8	TF5505x6
1/2	TF5505x8
5/8	TF5505x10
3/4	TF5505x12
7/8	TF5505x14
1	TF5505x16
1-1/4	TF5505x20
1-1/2	TF5505x24
2	TF5505x32

<sup>1</sup>5517x

<sup>1</sup>Special order only.

90° Bulkhead Union  
Elbow

(Ref. SAE No. 070701)  
Assembly Number C35525x4,  
etc.



TUBE O.D.	CATALOG NUMBER
1/4	C5525x4 <sup>1</sup>
5/16	C5525x5 <sup>1</sup>
3/8	C5525x6 <sup>1</sup>
1/2	C5525x8
5/8	C5525x10 <sup>1</sup>
3/4	C5525x12 <sup>1</sup>
1	C5525x16
1-1/4	C5525x20
1/4	TF5525x4
5/16	TF5525x5
3/8	TF5525x6
1/2	TF5525x8
5/8	TF5525x10
3/4	TF5525x12
1	TF5525x16

For bulkhead nut see page 257.

Included with assembly.

<sup>1</sup>5537x

<sup>1</sup>Special order only.

\*Stainless steel catalog number.

□ Available in Stainless Steel.

## Equipment

### Coll-O-Crimp Pumps

#### T-412 • Mobile Electric Pump



For use with T-400-1 and  
T-420-1.

#### Pump Specifications:

**Dimensions:** 7-1/2" high, 14-1/2" long, 9" wide

**Weight:** 65 lbs.

**Operation Pressure:** 4000-4200 PSI

**Reservoir Capacity:** 3 quarts

**Outlet Port Size:** 3/4"-16 straight thread

**Motor:** 2 volt D.C.


**Hydraulic Oil:** SAE 10W hydraulic oil or (ATF) Automatic Transmission Fluid

**Flow:** 0.5 GPM

#### Replacement Parts:

CATALOG NUMBER	DESCRIPTION
T-401-1B	Replacement Gasket between motor and square reservoir
T-401-1BC	Breather Cap for Fenner-Stone pumps

#### T-421U • Electric Pump (220 Volt)



For use with T-400-1 and  
T-420-1.

#### Pump Specifications:

**Dimensions:** 7-1/2" high, 22" long, 10" wide

**Weight:** 75 lbs.

**Operation Pressure:** 4000-4200 PSI

**Reservoir Capacity:** 6 quarts

**Outlet Port Size:** 3/4"-16 Straight Thread

**Motor:** 1 H.P., 3450 R.P.M., 220 volts, 60 cycle, single phase  
At 50 Hertz, RPM = 2,850  
At 60 Hertz, RPM = 3,450

**Hydraulic Oil\*:** ISO 32 hydraulic oil or (ATF) automatic transmission fluid

**Flow:** 2.5 GPM @ 750 PSI, 0.5 GPM @ 4000 PSI


**Note:** It is recommended that the electric pump be used on a 15 amp. fused circuit. Pump wired for 220 volts, single phase.

#### Replacement Parts:

CATALOG NUMBER	DESCRIPTION
140-06761	Relay for T-421U, T-441 and T-441 pumps only
T-421U-BC	Breather Cap
T-421-FP	220v 4 wire Female electrical receptacle

\*For low temperature applications automatic transmission fluid can be substituted.

#### T-421U-110 • Electric Pump (110 Volt)



For use with T-400-1 and  
T-420-1.

For dimensional data other than voltage information, refer to T-421U see above.

**Note:** It is recommended that the electric pump be used on an individual 30 amp. fused circuit.

Pump wired for 110 volts, single phase.

#### Replacement Parts:

CATALOG NUMBER	DESCRIPTION
T-421U-BC	Breather Cap
T-421-FP	220v 4 wire Female electrical receptacle