

Equipment

Coll-O-Crimp T-440



Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on page 3.



Reference pages 356-367 for Coll-O-Crimp tooling, tooling packages and pumps.

Note: Seal kits for T-410 and T-440 are not sold separately. Crimpers must be sent in and torqued by Weatherhead.

Refer to safety information regarding Coll-O-Crimp crimping procedures on pages 349-350.

The Coll-O-Crimp II Plus is ideal for factory, high performance machine operations, construction and mine locations. This machine offers the capabilities of crimping all of the crimp style hose ends Weatherhead offers. With this coverage, this heavy-duty crimper can handle all of your crimping needs.

CAUTION

The Coll-O-Crimp power source has the pressure relief valve set at 5000 PSI. Damage to the press will result if higher pressures are used and warranty may be voided.

Capacity: 3/16" I.D. 1 fiber braid through 2" 6 spiral hose; for hoses other than 4 and 6 spiral, conversion tooling is required. See page 356-361 for details.

Mounting: Bench

Size: 27" high, 12" wide, 21" deep

Weight: 450 lbs.

Pump Required (sold separately): T-441, see page 347.

Note: These packages include tooling to crimp H430 hose. For additional tooling order from pages 356-361.

Note: For T-410 press, use T-410-BB switch.

T-440-N • Coll-O-Crimp II Plus Package

Includes one each of the following:

CATALOG NUMBER	DESCRIPTION
T-440-1	C-O-C II Plus Press, T-440-M Instructions and 140-06741 Switch
T-441	220v 2-stage Electric Pump
T-410-4CN	430 'U' N/S Collet - 1/2" I.D.
T-410-5CN	430 'U' N/S Collet - 3/4" I.D.
T-410-6CN	430 'U' N/S Collet - 1" I.D.
T-410-7CN	430 'U' N/S Collet - 1-1/4" I.D.
T-410-8N	430 'U' N/S Collet - 1-1/2" I.D.
T-410-9N	430 'U' N/S Collet - 2" I.D.
T-410-22	36" Pump to Press Hose Assembly

Repair & Replacement Items:

CATALOG NUMBER	DESCRIPTION
T-410-26R	Base Plate Insert (7") (T-440-1)
T-410-26	Base Plate Insert (6") (T-410-1)
T-410-28	Tool Locator Bracket
T-410-B	Pusher Bolt and Washers
T-410-E	Shroud Decal
T-440-M	Instructions for T-440-1
T-410-P	Pusher Set (2) for T-410-1 and T-440-1
T-410-1M	Microswitch for T-410-1 & T-440-1
T-421-FP	4 prong female electrical outlet See page 245 for illustration.
T-400-G	1.5 oz. Tube High Efficiency * Grease
140-06741	Pump Switch for the T-440-1 crimper using T-441 pump
T-410-BB	Pump Switch for T-410-1 crimper using T-421U or T-421U-110 pump only

Equipment

Coll-O-Crimp Pumps

T-462-2 • Air/Hydraulic Pump



For use with T-462.

The Weatherhead T-462-2 power unit is a air/hydraulic pump designed for use with the T-462 portable system. Ideal if you have the availability of compressed air in your shop or in the field via a portable compressor.

Pump Specifications:

Dimensions: 4" high, 13" long

Weight: 8 lbs.

Operation Pressure: 0-10,000 PSI

Reservoir Capacity: 10 cu in.

Relief Valve Setting: 10,000 PSI

Hydraulic Oil: Use Enerpac Oil ONLY

Regulator to be set for 100-120 PSI inlet air.

T-480-2 • Two-Stage Hand Pump



For use with T-480-HP.

Pump Specifications:

Dimensions: 7-3/16" high x 21-1/64" long x 4-3/4" wide

Weight: 9 lbs.

Operation Pressure: 0-10,000 PSI

Hydraulic Oil: Use Enerpac Oil ONLY

T-480-3 • Turbo Air/ Hydraulic Pump



For use with T-480-TA.

Pump Specifications:

Dimensions: 8-1/4" High x 12-3/8" long x 8" wide

Weight: 16-1/2 lbs.

Operation Pressure: 0-10,000 PSI

Hydraulic Oil: Use Enerpac Oil ONLY

For repair and replacement items for the following pumps please contact an Enerpac Distributor at www.enerpac.com: T-402-2, T-403-2, T-460-2, T-462-2, T-480-2, T-480-3, T-481-110 & T-482-2.